characteristics Labsit 4 with sit-stop-castors and foot ring

Article: 9125E integral foam

Dimensions in mm	Backrest: H:		420
	Seat:	H:	560-810
		B:	450
		T:	420
Packing data	Weight Volume	kg m³	9,8

			•
55	V	3	0

Base equipment		Benefit
Lab qualification	Washable and disinfectant-proof GMP-compliant and suitable for clean rooms Can be used in labs in safety class S1 to S3. Joint-free and positive-fit elements (hygienic design)	Suitable for labs and all types of areas where hygiene is critical, as well as use in the healthcare sector, universities, biotechnology, chemistry and pharmaceuticals.
Conductivity	design). Conductive comfort pad typical leakage resistance of 10 up 6 Ohm. Volume-conducting castors.	Compliant with the ESD properties acc. to DIN EN 61340-5-1.
Handling	Practical handle on backrest. Extremely lightweight. Compact dimensions.	Ensures maximum mobility and simple handling.
Ergonomics	Only a single lever has to be operated for adaptation to the user and workplace situation.	Intuitive handling. Labsit can be automatically adapted with its flex functions. Complicated adjustment tasks are dispensed with.
Backrest	Plastic backrest with 3D flex function.	The backrest is adapted to the movements of the user and gives way when reclining and during lateral rotation of the upper body. Thus ensuring dynamic sitting and optimal body support in every sitting posture. Intuitive and automatic.
Seating surface	Flex function in front edge of seat.	The front edge of the seat is automatically readjusted for leaning forward. As a result, pressure loading is prevented and blood circulation is improved.
Seat shell	Black.	Distinctive appeal. Increase in job quality and employee satisfaction.
Seat pad	ESD integral foam pad (PU): The integral foam pad offers maximum resistance and ease of cleaning. Extremely robust, durable, washable, disinfectant-proof, PVC-free, resistant to blood and urine, fire protection acc. to EN 1021 Parts 1 + 2, black colour.	Recommended use in environments where one comes into contact with aggressive working materials. The surface is resistant, extremely robust, washable and easy to clean. Resistant to pointed and sharp objects.
Seat height	Seat height setting, infinitely variable from 560 - 810 mm.	Large seat height adjustment range.
Base	Aluminium base.	Very high stability, durable and stable. Elegant and high-quality.
Foot ring	Chrome height-adjustable foot ring.	Provides support thanks to the wide step area and the height can be adjusted simply and quickly.

bimos

characteristics Labsit 4 with sit-stop-castors and foot ring

Article: 9125E integral foam

Dimensions in mm	Backrest:	H:	420	
	Seat:	H:	560-810	4
		B:	450	
		T:	420	V
Packing data	Weight	kg	9,8	
	Volume	m³		55533
Castors		Soft seat-s	top castors for hard floors.	Held in place with load, rollable with no load.
Standards		purity class S1 to S3 Ti 68 877-1 G Angel Sani ISO 9001 E ISO 14001 EMAS Indu 18001 Eco	340-5-1 DIN EN ISO 14644-1 Air 3 GMP-compliant Lab safety class ested for harmful substances DIN S certificate for "tested safety" Blue tized Quality management DIN EN Environmental management DIN EN Tested environmental management ustrial safety management OHSAS Vadis CSR Rating 2016 Gold	Verified by certificates from independent testing institutes Procurement security
Guarantee			ig-term guarantee, of which 3-year	Assured quality and high efficiency

characteristics Labsit 4 with sit-stop-castors and foot ring

Article: 9125E integral foam

Armrests

Dimensions in mm	Backrest:	H:	420
	Seat:	H:	560-810
		B:	450
		T:	420
Packing data	Weight	kg	9,8
	Volume	m³	

Fixed armrests

	Benefit
and individual marking. Can be ched and removed at any time	Customizable and can therefore be clearly assigned to an occupier or area.

Made from plastic

Accessories/Labclip			and individual marking. Can be hed and removed at any time	Customizable and can therefore be clearly an occupier or area.
Options				Benefit
Packing data	Weight Volume	kg m³	9,8	4
		T:	420	
		B:	450	



.