

characteristics ESD Labsit stool with castors

Article: 9127E integral foam

Dimensions in mm

Seat:	H:	450-650
	B:	400
	T:	400

Packing data	Weight	kg	7,4
	Volume	m ³	



Base equipment

Benefit

Conductivity	Conductive comfort pad typical leakage resistance of 10 up 6 Ohm. Volume-conducting castors.	Compliant with the ESD properties acc. to DIN EN 61340-5-1, 100% ESD safe.
Lab qualification	Washable and disinfectant-proof GMP-compliant and suitable for clean rooms Can be used in labs in safety class S1 to S3 Joint-free and positive-fit elements (hygienic design).	Suitable for labs and all types of areas where hygiene is critical, as well as use in the healthcare sector, universities, biotechnology, chemistry and pharmaceuticals.
Seat pad	ESD integral foam pad (PU): The integral foam pad offers maximum resistance and ease of cleaning. Extremely robust, durable, washable, disinfectant-proof, PVC-free, resistant to blood and urine, fire protection acc. to EN 1021 Parts 1 + 2, black colour.	Recommended use in environments where one comes into contact with aggressive working materials. The surface is resistant, extremely robust, washable and easy to clean. Resistant to pointed and sharp objects.
Seat height	Seat height setting, infinitely variable from 450 - 650 mm.	Large seat height adjustment range.
Base	Aluminium base.	Very high stability, durable and stable. Elegant and high-quality.
Castors/Glides	Load-dependent braked, soft double castors for hard floors.	Chair does not roll away when unloaded, thus minimised risk of accident.
Standards	DIN EN 61340-5-1 DIN EN ISO 14644-1 Air purity class 3 GMP-compliant Lab safety class S1 to S3 Tested for harmful substances DIN 68 877-1 GS certificate for "tested safety" Blue Angel Sanitized Quality management DIN EN ISO 9001 Environmental management DIN EN ISO 14001 Tested environmental management EMAS Industrial safety management OHSAS 18001 EcoVadis CSR Rating 2016 Gold.	Verified by certificates from independent testing institutes. Procurement security.
Guarantee	10-year long-term guarantee, of which 3-year full warranty.	Assured quality and high efficiency.