

characteristics Cleanroom Stool 1 with glides

Article: 9467R artificial leather

Dimensions in mm

Seat:	H:	460-630
	B:	400
	T:	400



Packing data

Weight	kg	6,5
Volume	m ³	0,13

Base equipment

Benefit

Suitability for cleanrooms	Air purity level 3 according to DIN EN ISO 14644-1 Air purity level 1 according to US-Fed St. 209E Sealed upholstery with special foam technology Materials that are suitable for use in clean rooms Smooth, sealed surfaces.	Certified suitability for clean rooms. It can be ensured that no particles are emitted. The build-up of particles on the chair are avoided.
Conductivity	The metal components have a conductive coating Volume conductive plastic parts The high-comfort upholstery is also conductive Typical discharge resistance of 10 ⁶ Ohm Conductive glides.	Exceeds the requirements of ESD protection according to standard DIN EN 61340-5-1. 100% ESD protection.
Seat	Extra large seat with a diameter of 400 mm.	Automatically encourages healthy posture and upright seating. The round front edge of the seat prevents blocked circulation in the thighs.
Finishes for seat	ESD synthetic leather upholstery: High-level ESD synthetic leather Skai Tundra. Resistant to desinfectants, washable and easy-care Colour: black (2571).	The soft and comfortable upholstery provides a comfortable feel. However, damages caused by sharp parts can not be excluded. Ideal for the use in production and laboratory.
Seat height	Stepless seat height setting from 460 - 630 mm supported by safety gas spring with protective cover.	Seat height can be adapted to nearly 95 % of all body sizes, the cover protects the gas spring from dust and dirt.
Functions / Mechanism	Ring release.	Height adjustment can be operated comfortable and easy in sitting position.
Base	The chairs are supplied with a brilliantly polished and wearproof aluminium 5 star base.	Very high stability, longevity.
Glides	Wearproof plastic glides with a large surface area. Conductive.	Offer a superb level of stability.
Materials	The materials used are recyclable.	Environmentally friendly.
Standards	DIN EN ISO 14644-1 DIN 61340-5-1 DIN 68 877 German GS "safety tested" mark of confirmity Quality Management System DIN EN ISO 9001 Regulation EWG Nr. 1836/93 Environmental Management System DIN EN ISO 14001.	Certified suitability for clean rooms 100% ESD protection Procuring is insured.
Warranty	10 year long term warranty, 3 years full warranty.	Guaranteed quality and high efficiency.